

*Signature Packaging Machinery, Inc.* <sup>TM</sup>  
"Signature of Excellence"



**Unique Features Of The Signature Shrink Tunnels:**

1. All tunnels are equipped with solid-state precision heat controllers. All the heaters individually pulse and sense the heat in the chamber to insure consistent temperature control within a few degrees. This allows the operator to set temperatures even at low settings to shrink soft films and sensitive packages, unlike other models that utilize certain heaters to stay active at all times.
2. All tunnels with easy access to blower motors and bearings, which are located on the outside of the chamber. Heaters are easily accessible by removing the side panels. All tunnels are sealed and insulated to maintain cool outer surfaces.
3. All tunnels are built from a welded steel chassis to insure heavy-duty production use 24 hours a day, seven days a week.
4. Signature utilizes a variety of belt designs, including the standard nomex mesh belt that has no steel wire alligator splicing or flaps to leave marks on the bottom of the package. Each package exits the tunnel with a smooth film finish on top and bottom.
5. Each tunnel is equipped with heavy duty 1 and 1.5 horsepower blower motors and four sided air flow to provide the best air velocity and lowest heat consumption of any tunnel available today. These tunnels usually will shrink films at temperatures fifty degrees less than other models, reducing electrical consumption in the plant.